LABELS THAT GO FURTHER

Fusion Transfer

RT225P02

FUSION

FACESHEET

Basis Weight (lb/ream)	
Caliper Target (mils)	2.9
Tensile MD Target (lb/in)	28
Tensile CD Target (lb/in)	17
Tear MD (grams)	40
Tear CD (grams)	50
Stiffness MD (grams)	
Stiffness CD (grams)	
Color	White

ADHESIVE

Description	Hot Melt Rubber Permanent
Caliper Target (mils)	0.7

LINER

Description	Glassine
Caliper Target (mils)	1.6

TOTAL CALIPER

Caliper Target (mils)	5.2

FACESHEET TYPE

- ✓ Paper
- Film

PRODUCT TYPE

- ✓ Label
- Tag
- Receipt

IMAGING CAPABILITY

- Inkjet
- Direct Thermal
- ✓ Thermal Transfer - Wax
- ✓ Thermal Transfer - Wax/Resin
- Thermal Transfer - Resin
- Laser

AGENCY RECOGNITION

- BS 5609
- UL
- cUL
- ✓ FSC® C172051
- ✓ FDA.21 CFR 175.105
- BPA Free
- Prop 65 - BPA & BPS Free

SUGGESTED OUTDOOR LIFE

- ✓ For Indoor Use only
- <6 months
- <12 months
- <18 months
- 2+ years

ENVIRONMENT

Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	35		
Service Temperature (°F)	-65	to	150

SPECIAL NOTES: Fusion labels deliver cost effective performance across a wide variety of applications, with more labels per roll to reduce waste and downtime.

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

SATO AMERICA
CORPORATE
14125 South Bridge Circle
Charlotte, NC 28273
Phone: (704) 644-1650
sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES
UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

9007049

www.satoamerica.com

©2026 SATO America. All rights Reserved. • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.

1/6/2026