

# SATO-Direct 200P

RD200P01

## FACESHEET

Basis Weight (lb/ream)	51
Caliper Target (mils)	3.2
Tensile MD Target (lb/in)	28
Tensile CD Target (lb/in)	14
Tear MD (grams)	
Tear CD (grams)	
Stiffness MD (grams)	
Stiffness CD (grams)	
Color	White

## ADHESIVE

Description	Tackified Acrylic Permanent
Caliper Target (mils)	0.5

## LINER

Description	40# White Kraft
Caliper Target (mils)	2.4

## TOTAL CALIPER

Caliper Target (mils)	6.1
-----------------------	-----

## ENVIRONMENT

Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	32		
Service Temperature (°F)	-4	to	120

## SPECIAL NOTES:

## FACESHEET TYPE

- ✓ Paper
- Film

## PRODUCT TYPE

- ✓ Label
- Tag
- Receipt

## IMAGING CAPABILITY

- Inkjet
- ✓ Direct Thermal
- Thermal Transfer - Wax
- Thermal Transfer - Wax/Resin
- Thermal Transfer - Resin
- Laser

## AGENCY RECOGNITION

- BS 5609
- UL
- cUL
- ✓ FSC® C172051
- FDA.21 CFR 175.105
- ✓ BPA Free
- ✓ Prop 65 - BPA & BPS Free

## SUGGESTED OUTDOOR LIFE

- ✓ For Indoor Use only
- <6 months
- <12 months
- <18 months
- 2+ years

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

## SATO AMERICA

### CORPORATE

14125 South Bridge Circle  
Charlotte, NC 28273  
Phone: (704) 644-1650  
[sales-sal@sato-global.com](mailto:sales-sal@sato-global.com)

### LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA  
CANADA CARIBBEAN

[www.satoamerica.com](http://www.satoamerica.com)

©2025 SATO America . All rights Reserved. • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.