

SATO-Transfer 200P

RT200P01

FACESHEET				
Basis Weight (lb/ream)				
Caliper Target (mils)	2.9	2.9		
Tensile MD Target (lb/in)	28	28		
Tensile CD Target (lb/in)	17	17		
Tear MD (grams)	40	-		
Tear CD (grams)	50			
Stiffness MD (grams)	150			
Stiffness CD (grams)	100			
Color	White	White		
ADHESIVE				
Description	Emulsion Acrylic			
		anent	.,	
Caliper Target (mils)	0.7			
LINER				
Description	40# S	40# SCK		
Caliper Target (mils)	2.4			
TOTAL CALIBER				
TOTAL CALIPER				
Caliper Target (mils)	6			
ENVIRONMENT				
Storage Temperature (°F)	40	to	72	
Storage Humidity (%RH)	35	to	75	
Shelf Life (months)	12			
Min Application Temp (°F)	25			
Service Temperature (°F)	-75	to	200	

FACESHEET TYPE

✓ Paper Film

PRODUCT TYPE

✓ Label Tag Receipt

IMAGING CAPABILITY

Inkjet

Direct Thermal

- ✓ Thermal Transfer Wax
- ✓ Thermal Transfer Wax/Resin Thermal Transfer - Resin

Laser

AGENCY RECOGNITION

BS 5609 UL cUL

FSC® C172051

✓ FDA.21 CFR 175.105

BPA Free

Prop 65 - BPA & BPS Free

SUGGESTED OUTDOOR LIFE

✓ For Indoor Use only

<6 months

<18 months

2+ years

SPECIAL NOTES:

Adhesive is considered to be latex glove friendly.

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

SATO AMERICA

CORPORATE

14125 South Bridge Circle Charlotte, NC 28273 Phone: (704) 644-1650 sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com