

# SF100 Polypropylene

RT400P01

## FACESHEET

Basis Weight (lb/ream)	
Caliper Target (mils)	2.6
Tensile MD Target (lb/in)	13.5
Tensile CD Target (lb/in)	27.5
Tear MD (grams)	
Tear CD (grams)	
Stiffness MD (grams)	22
Stiffness CD (grams)	
Color	White

## ADHESIVE

Description	Emulsion Acrylic Permanent
Caliper Target (mils)	0.8

## LINER

Description	40# BG
Caliper Target (mils)	2.11

## TOTAL CALIPER

Caliper Target (mils)	5.51
-----------------------	------

## ENVIRONMENT

Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	23		
Service Temperature (°F)	-20	to	200

## SPECIAL NOTES:

## FACESHEET TYPE

	Paper
✓	Film

## PRODUCT TYPE

✓	Label
	Tag
	Receipt

## IMAGING CAPABILITY

	Inkjet
	Direct Thermal
	Thermal Transfer - Wax
✓	Thermal Transfer - Wax/Resin
	Thermal Transfer - Resin
	Laser

## AGENCY RECOGNITION

	BS 5609
	UL
	cUL
	FSC® C172051
✓	FDA.21 CFR 175.105
	BPA Free
	Prop 65 - BPA & BPS Free

## SUGGESTED OUTDOOR LIFE

	For Indoor Use only
	<6 months
✓	<12 months
	<18 months
	2+ years

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

## SATO AMERICA

### CORPORATE

14125 South Bridge Circle  
Charlotte, NC 28273  
Phone: (704) 644-1650  
[sales-sal@sato-global.com](mailto:sales-sal@sato-global.com)

### LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA  
CANADA CARIBBEAN

[www.satoamerica.com](http://www.satoamerica.com)

©2025 SATO America . All rights Reserved. • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.